

CLASS B (6 BAR)

CLASS C (9 BAR)

CLASS D (12 BAR)

CLASS E (15 BAR)

| Nominal Size | Outside Diameter (mm) | Wall Thickness (mm) | Weight (Kg/m) | Wall Thickness (mm) | Weight (Kg/m) | Wall Thickness (mm) | Weight (Kg/m) | Wall Thickness (mm) | Weight (Kg/m) |
|--------------|-----------------------|---------------------|---------------|---------------------|---------------|---------------------|---------------|---------------------|---------------|
| 1/2" | 21.2 | | | | | | | 1.7 | 0.16 |
| 3/4" | 26.6 | | | | | | | 1.9 | 0.23 |
| 1" | 33.4 | | | | | | | 2.2 | 0.33 |
| 1 1/4" | 42 | | | | | 2.2 | 0.41 | 2.7 | 0.51 |
| 1 1/2" | 48.1 | | | | | 2.5 | 0.54 | 3.1 | 0.66 |
| 2" | 60.2 | | | 2.5 | 0.68 | 3.1 | 0.83 | 3.9 | 1.03 |
| 3" | 88.7 | 2.9 | 1.17 | 3.5 | 1.4 | 4.8 | 1.82 | 5.7 | 2.21 |
| 4" | 114.1 | 3.4 | 1.77 | 4.5 | 2.32 | 6 | 3.03 | 7.3 | 3.63 |
| 6" | 168 | 4.5 | 3.45 | 6.6 | 5.00 | 8.8 | 6.54 | 10.8 | 7.92 |
| 8" | 218.8 | 5.3 | 5.27 | 7.8 | 7.69 | 10.3 | 10 | 12.6 | 12.13 |

PRODUCED ON REQUEST

1/2" - 1 1/2":

Solvent cement socket only

2" - 8":

Solvent cement socket or Rubber ring joint

Length:

Standard 6m 5.8m for export packing

Colour:

Grey or Black