

CLASS 3 (6 BAR)

CLASS 4 (10 BAR)

CLASS 5 (16 BAR)

Outside Diameter (mm)	Nominal Wall Thickness (mm)	Nominal Weight (kg/m)	Nominal Wall Thickness (mm)	Nominal Weight (kg/m)	Nominal Wall Thickness (mm)	Nominal Weight (kg/m)
20					1.5	0.137
25					1.9	0.212
32			1.6	0.24	2.4	0.342
40			1.9	0.35	3.0	0.525
50			2.4	0.55	3.7	0.809
63	1.9	0.562	3.0	0.854	4.7	1.289
75	2.2	0.782	3.6	1.22	5.6	1.82
90	2.7	1.13	4.3	1.75	6.7	2.61
110	2.7	1.40	4.2	2.12	6.6	3.23
125	3.1	1.82	4.8	2.75	7.4	4.11
140	3.5	2.29	5.4	3.45	8.3	5.16
160	4	2.99	6.2	4.52	9.5	6.73
200	4.9	4.55	7.7	7.00	11.9	10.52
225	5.5	5.74	8.6	8.79	13.4	13.32
250	6.2	7.17	9.6	10.89	14.8	16.34
315	7.7	11.2	12.1	17.25	18.7	25.98
355	8.7	14.40	13.6	21.9	21.1	33.10
400	9.8	18.05	15.3	27.67	23.7	41.78

20mm - 50mm Solvent cement socket only

63mm - 400mm Solvent cement socket or Rubber ring joint

Length: Standard 6m. 5.8m for export packing

Colour: Grey or Black