

Outside Diameter (mm)	Nominal Wall Thickness (mm)	CLASS 2 (4 BAR)		CLASS 3 (6 BAR)		CLASS 4 (10 BAR)		CLASS 5 (16 BAR)	
		Nominal Weight (kg/m)	Nominal Wall Thickness (mm)	Nominal Weight (kg/m)	Nominal Wall Thickness (mm)	Nominal Weight (kg/m)	Nominal Wall Thickness (mm)	Nominal Weight (kg/m)	Nominal Wall Thickness (mm)
20								1.5	0.137
25						1.5	0.174	1.9	0.212
32						1.8	0.264	2.4	0.342
40			1.8	0.334	1.9	0.35	3	0.525	
50			1.8	0.422	2.4	0.55	3.7	0.809	
63			1.9	0.562	3.6	0.854	4.7	1.289	
75	1.8	0.642	2.2	0.782	3.6	1.22	5.6	1.820	
90	1.8	0.774	2.7	1.13	4.3	1.75	6.7	2.61	
110	2.2	1.16	3.2	1.64	5.3	2.61	8.2	3.90	
125	2.5	1.5	3.6	2.11	6.0	3.38	9.2	5.01	
140	2.8	1.84	4.1	2.65	6.7	4.10	10.4	6.27	
160	3.2	2.41	4.7	3.44	7.7	5.47	11.9	8.17	
200	4.0	3.7	5.9	5.37	9.6	8.51	14.9	12.8	
225	4.5	4.7	6.6	6.76	10.8	10.8	16.9	16.1	
250	4.9	5.65	7.3	8.31	11.9	13.2	18.6	19.9	
315	6.2	9.02	9.2	13.10	15	20.9	23.8	32.45	
400	7.9	14.5	11.7	21.10	19.1	34	29.7	50.8	

PRODUCED ON REQUEST

20mm - 50mm

Solvent cement socket only

63mm - 400mm:

Solvent cement socket or Rubber ring joint

Length:

Standard 6m 5.8m for export packing

Colour:

Grey or Black